

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 January 2004 (29.01.2004)

PCT

(10) International Publication Number
WO 2004/009924 A1

(51) International Patent Classification⁷: **E04B 1/84**,
E04C 2/24, B32B 7/02

Miles [GB/GB]; Peartree Cottage, 23 Sherbourne, Cheltenham, Gloucestershire GL54 3DR (GB). **DAVIDSON, Roger** [GB/GB]; 5 Cornavill Close, Abingdon, Oxfordshire OX14 2ND (GB).

(21) International Application Number:
PCT/GB2003/002719

(22) International Filing Date: 26 June 2003 (26.06.2003)

(74) Agents: **FRENCH, Clive et al.**; Siemens Plc, P O Box 22 16 34, 80506 Munich (DE).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0216849.0 19 July 2002 (19.07.2002) GB

(71) Applicants (for all designated States except US): **OXFORD MAGNET TECHNOLOGY LTD** [GB/GB]; Wharf Road, Eynsham, Oxford, Oxfordshire OX8 1BP (GB). **CROMPTON TECHNOLOGY GROUP LTD** [GB/GB]; Thorpe Park, Thorpe Way, Banbury, Oxfordshire OX16 4SU (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(72) Inventors; and

(75) Inventors/Applicants (for US only): **ATKINS, Andrew, Farquhar** [GB/GB]; 5 Bennett Close, Chacombe, Banbury, Oxfordshire OX17 2JZ (GB). **CUMNER, Geoffrey**,

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: COMPOSITE MATERIAL FOR ACOUSTIC DAMPING



(57) Abstract: A composite material (10) for acoustic or mechanical damping, comprising: a plurality of layers (12) of fibrous material embedded in a solid material (14), characterised in that the solid material has a composition which varies through a depth of the material, the composition having a relatively high proportion of a first material (18), being a structural composite resin, and a relatively low proportion of a second material (16), being a material of high hysteretic loss, at the outer surfaces of the material, and the composition having a damping region (24) between the outer surfaces wherein the composition has a relatively high proportion of the second material and a relatively low proportion of the first material, the composition, the composition of the solid material varying through a gradual change in composition between the damping region and the outer surfaces, such that the material contains no abrupt changes in composition

WO 2004/009924 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.